

# HPV 900

S E R I E S T W O



## AC Elevator Drive

Magnetek's HPV 900 Series 2 elevator drive continues the tradition of high performance, high overload capacity and long-life reliability. It is designed for both new installations and modernization projects, and provides advanced closed-loop vector control for superior performance. The HPV 900 Series 2 offers the fastest, easiest set-up adjustment; fewest callbacks; and the lowest total lifetime cost. This cost-effective AC drive gives you accurate acceleration and deceleration resulting in smooth ride quality. Magnetek's proven technical expertise plus our superior customer service has placed us as the world's leading source of innovative, built-to-last elevator drives.



**MAGNETEK**  
E L E V A T O R

## DESIGNED AND RATED FOR ELEVATOR APPLICATIONS

- No oversizing needed
- Designed with high overload capacity (250%)
- An internal dynamic braking IGBT
- Cooling fans run only when drive is in operation

## ELEVATOR APPLICATION SOFTWARE AND PARAMETERS

- Offering the ultimate performance features
- Unique elevator speed regulator
- Parameters are in elevator industry terminology

## EASY SET-UP

- No need for mechanical disconnect to tune critical motor parameters
- Parameter upload/download software
- Drive calculates elevator system inertia
- Configurable I/O channels
- Easy parameter changes via digital operator

## HPV 900 SERIES 2 AC ELEVATOR DRIVE PRODUCT DATA

Rated Input Voltage	Rated (HP)	Rated (kW)	Continuous Output Current General Purpose Rating	Continuous Output Current Elevator Duty Cycle Rating	Maximum Output Current for 5 sec	Height	Width	Depth
380 - 480 VAC	5	3.7	8	8.6	20	11.02in (280mm)	7.28in (185mm)	7.36in (187mm)
	5.5	4	12	12.8	30	12.6in (320mm)	9.05in (230mm)	8.27in (210mm)
	7.5	5.5	16	17.1	40			
	10	7.5	21	22.5	52.5	15.6in (396mm)	10.4in (265mm)	9in (227mm)
	15	11	27	28.9	67.5			
	20	15	34	36.4	85	21.1in (536mm)	8.82in (224mm)	12.24in (311mm)
	25	18.5	41	43.9	102.5			
	30	22	52	55.6	130			
	40	30	65	69.6	162.5	27.28in (693mm)	12.8in (325mm)	13.23in (336mm)
	50	37	72	77.0	180			
	60	45	96	102.7	240			

- All ratings at 60/50Hz and 10kHz carrier frequency
- All models include internal dynamic braking IGBT
- Operating temperature: -10°C (14°F) to 45°C (113°F)
- Standards: CSA and CE



Magnetek Ltd. (UK)  
20 Drake Mews, Crownhill  
Milton Keynes, Buck MK8 OER UK  
p +44(0) 1908 261427  
f +44(0) 1908 261674

Magnetek Elevator (US)  
N50 W13605 Overview Drive  
Menomonee Falls, WI 53051  
800.236.1705  
p 262.252.6999  
f 262.790.4142